



PRESSURE GAUGES

HEAVY VERSIONS



Case:
Stainless steel, W 1.4301

Glass: Acryl
Accuracy: +/-1,0 %

Movement:
Brass

Max.process temperature:
60 °C

Measuring system:
Bourdon-tube, brass W 2.1030
up to 60 bar
Stainless steel W 1.4571
100...600 bar

Code	Type	Diam.	Ranges	Connect	Materials
10401-BA	401	100	-1 - 0 bar	G1/2 Radial	SS / Brass
10401-BB	401	100	-1 - 1,5 bar	G1/2 Radial	SS / Brass
10401-BC	401	100	-1 - 3 bar	G1/2 Radial	SS / Brass
10401-BD	401	100	-1 - 5 bar	G1/2 Radial	SS / Brass
10401-BE	401	100	-1 - 9 bar	G1/2 Radial	SS / Brass
10401-BF	401	100	-1 - 15 bar	G1/2 Radial	SS / Brass
10401-BG	401	100	0 - 0,6 bar	G1/2 Radial	SS / Brass
10401-BH	401	100	0 - 1 bar	G1/2 Radial	SS / Brass
10401-BI	401	100	0 - 1,6 bar	G1/2 Radial	SS / Brass
10401-BJ	401	100	0 - 2,5 bar	G1/2 Radial	SS / Brass
10401-BK	401	100	0 - 4 bar	G1/2 Radial	SS / Brass
10401-BL	401	100	0 - 6 bar	G1/2 Radial	SS / Brass
10401-BM	401	100	0 - 10 bar	G1/2 Radial	SS / Brass
10401-BN	401	100	0 - 16 bar	G1/2 Radial	SS / Brass
10401-BO	401	100	0 - 25 bar	G1/2 Radial	SS / Brass
10401-BP	401	100	0 - 40 bar	G1/2 Radial	SS / Brass
10401-BQ	401	100	0 - 60 bar	G1/2 Radial	SS / Brass
10401-BR	401	100	0 - 100 bar	G1/2 Radial	SS / Brass
10401-BS	401	100	0 - 160 bar	G1/2 Radial	SS / Brass
10401-BT	401	100	0 - 250 bar	G1/2 Radial	SS / Brass
10401-BU	401	100	0 - 315 bar	G1/2 Radial	SS / Brass
10401-BV	401	100	0 - 400 bar	G1/2 Radial	SS / Brass
10401-BX	401	100	0 - 600 bar	G1/2 Radial	SS / Brass
10401-BY	401	100	0 - 1000 bar	G1/2 Radial	SS / Brass
10411-BA	411	100	-1 - 0 bar	G1/2 Axial	SS / Brass
10411-BB	411	100	-1 - 1,5 bar	G1/2 Axial	SS / Brass
10411-BC	411	100	-1 - 3 bar	G1/2 Axial	SS / Brass
10411-BD	411	100	-1 - 5 bar	G1/2 Axial	SS / Brass
10411-BE	411	100	-1 - 9 bar	G1/2 Axial	SS / Brass
10411-BF	411	100	-1 - 15 bar	G1/2 Axial	SS / Brass
10411-BH	411	100	0 - 1 bar	G1/2 Axial	SS / Brass
10411-BI	411	100	0 - 1,6 bar	G1/2 Axial	SS / Brass
10411-BJ	411	100	0 - 2,5 bar	G1/2 Axial	SS / Brass
10411-BK	411	100	0 - 4 bar	G1/2 Axial	SS / Brass
10411-BL	411	100	0 - 6 bar	G1/2 Axial	SS / Brass
10411-BM	411	100	0 - 10 bar	G1/2 Axial	SS / Brass
10411-BN	411	100	0 - 16 bar	G1/2 Axial	SS / Brass
10411-BO	411	100	0 - 25 bar	G1/2 Axial	SS / Brass
10411-BP	411	100	0 - 40 bar	G1/2 Axial	SS / Brass
10411-BQ	411	100	0 - 60 bar	G1/2 Axial	SS / Brass
10411-BR	411	100	0 - 100 bar	G1/2 Axial	SS / Brass
10411-BS	411	100	0 - 160 bar	G1/2 Axial	SS / Brass
10411-BT	411	100	0 - 250 bar	G1/2 Axial	SS / Brass
10411-BU	411	100	0 - 315 bar	G1/2 Axial	SS / Brass
10411-BV	411	100	0 - 400 bar	G1/2 Axial	SS / Brass
10411-BX	411	100	0 - 600 bar	G1/2 Axial	SS / Brass

Lyth-Instrument Oy
Peltosaarekatu 8
FI-11130 Riihimäki
Finland , Europe

phone: + 358-19-760330
fax : + 358-19-722085
www.lyth.fi



PRESSURE GAUGES

HEAVY VERSIONS



Case:
Stainless steel, W 1.4301

Glass: Acryl
Accuracy: +/-1,0 %

Movement:
Brass

Max.process temperature:
60°C

Measuring system:
Bourdon-tube, brass W 2.1030
up to 60 bar
Stainless steel W 1.4571
100...600 bar

Code	Type	Diam.	Ranges	Connect	Materials
16401-BA	401	160	-1 - 0 bar	G1/2 Radial	SS / Brass
16401-BC	401	160	-1 - 3 bar	G1/2 Radial	SS / Brass
16401-BD	401	160	-1 - 5 bar	G1/2 Radial	SS / Brass
16401-BE	401	160	-1 - 9 bar	G1/2 Radial	SS / Brass
16401-BF	401	160	-1 - 15 bar	G1/2 Radial	SS / Brass
16401-BH	401	160	0 - 1 bar	G1/2 Radial	SS / Brass
16401-BI	401	160	0 - 1,6 bar	G1/2 Radial	SS / Brass
16401-BJ	401	160	0 - 2,5 bar	G1/2 Radial	SS / Brass
16401-BK	401	160	0 - 4 bar	G1/2 Radial	SS / Brass
16401-BL	401	160	0 - 6 bar	G1/2 Radial	SS / Brass
16401-BM	401	160	0 - 10 bar	G1/2 Radial	SS / Brass
16401-BN	401	160	0 - 16 bar	G1/2 Radial	SS / Brass
16401-BO	401	160	0 - 25 bar	G1/2 Radial	SS / Brass
16401-BP	401	160	0 - 40 bar	G1/2 Radial	SS / Brass
16401-BQ	401	160	0 - 60 bar	G1/2 Radial	SS / Brass
16401-BR	401	160	0 - 100 bar	G1/2 Radial	SS / Brass
16401-BS	401	160	0 - 160 bar	G1/2 Radial	SS / Brass
16401-BT	401	160	0 - 250 bar	G1/2 Radial	SS / Brass
16401-BV	401	160	0 - 400 bar	G1/2 Radial	SS / Brass
16401-BX	401	160	0 - 600 bar	G1/2 Radial	SS / Brass

Lyth-Instrument Oy
Peltosaarekatu 8
FI-11130 Riihimäki
Finland , Europe

phone: + 358-19-760330
fax : + 358-19-722085
www.lyth.fi